


Rollendes Rad: Zykloide (Bewegungsgleichungen)

Rollendes Rad: Gleichung d. Zykloide



$$x = s = r \cdot \varphi \quad ; \quad \frac{a}{2} = r \cdot \sin \frac{\varphi}{2} \Rightarrow a = 2 \cdot r \cdot \sin \frac{\varphi}{2}$$

$$\sin \frac{\varphi}{2} = \frac{y_P}{a} \Rightarrow y_P = a \cdot \sin \frac{\varphi}{2} = 2r \cdot \sin^2 \frac{\varphi}{2}$$

$$(x - x_P)^2 + y_P^2 = a^2$$

$$(x - x_P)^2 = a^2 - y_P^2$$

$$(x - x_P)^2 = \left(2r \sin \frac{\varphi}{2}\right)^2 - \left(2r \sin^2 \frac{\varphi}{2}\right)^2$$

$$= \left(2r \sin \frac{\varphi}{2}\right)^2 \left[1 - \sin^2 \frac{\varphi}{2}\right]$$

$$x - x_P = 2r \sin \frac{\varphi}{2} \cdot \sqrt{1 - \sin^2 \frac{\varphi}{2}}$$

$$x_P = x - 2r \sin \frac{\varphi}{2} \cdot \cos \frac{\varphi}{2}$$

$$x_P = r \cdot \varphi - 2r \sin \frac{\varphi}{2} \cdot \cos \frac{\varphi}{2}$$

$$\vec{r}_P = r \begin{bmatrix} \varphi - 2 \sin \frac{\varphi}{2} \cdot \cos \frac{\varphi}{2} \\ 2 \sin^2 \frac{\varphi}{2} \end{bmatrix}$$

$$\text{mit } \varphi = \omega \cdot t$$

$$\vec{v}_P = \begin{bmatrix} \dot{x}_P \\ \dot{y}_P \end{bmatrix} = \omega \cdot r \begin{bmatrix} 1 + \left(\sin^2 \frac{\omega t}{2} - \cos^2 \frac{\omega t}{2}\right) \\ 2 \cdot \sin \frac{\omega t}{2} \cdot \cos \frac{\omega t}{2} \end{bmatrix}$$

V aus Trans + Rot.


Kontrolle

$$\vec{V}_{\text{ges}} = \vec{V}_{\text{trans}} + \vec{V}_{\text{rot}}$$

$$\vec{V}_{\text{ges}} = \omega \cdot \vec{r} + \omega \cdot \vec{r}$$

$$\vec{V}_{\text{ges}} = 30 \frac{\text{mm}}{\text{s}} + 30 \frac{\text{mm}}{\text{s}}$$

$$\vec{V}_{\text{ges}} = 424 \frac{\text{mm}}{\text{s}} \text{ unter } 45^\circ$$



Kontrolle

$$r = 30 \text{ mm}$$

$$\varphi = 90^\circ$$

$$\frac{\varphi}{2} = 45^\circ$$


$$\vec{r} = \begin{bmatrix} 17,1 \text{ mm} \\ 30 \text{ mm} \end{bmatrix}$$

Geschw mit $\omega = 1 \frac{1}{\text{s}}$

$$\vec{V}_P = \begin{bmatrix} \dot{x}_P \\ \dot{y}_P \end{bmatrix} = 30 \frac{\text{mm}}{\text{s}} \begin{bmatrix} 1 + (\sin^2 45^\circ - \cos^2 45^\circ) \\ 2 \cdot \sin 45^\circ \cdot \cos 45^\circ \end{bmatrix}$$

$$= 30 \frac{\text{mm}}{\text{s}} \begin{bmatrix} 1 + 0 \\ 2 \cdot 0,5 \end{bmatrix}$$

$$= 30 \frac{\text{mm}}{\text{s}} \begin{bmatrix} 1 \\ 1 \end{bmatrix} = \begin{bmatrix} 30 \frac{\text{mm}}{\text{s}} \\ 30 \frac{\text{mm}}{\text{s}} \end{bmatrix}$$



$$\vec{a}_P = \begin{bmatrix} \ddot{x}_P \\ \ddot{y}_P \end{bmatrix}$$

$$\ddot{x}_P = a_x = \omega \cdot r \left[\cancel{2 \cdot \sin \frac{\omega t}{2} \cdot \cos \frac{\omega t}{2} \cdot \frac{\omega}{2}} + \cancel{2 \cos \frac{\omega t}{2} \cdot \sin \frac{\omega t}{2} \cdot \frac{\omega}{2}} \right]$$


$$\ddot{x}_P = \omega^2 \cdot r \cdot 2 \cdot \sin \frac{\omega t}{2} \cdot \cos \frac{\omega t}{2}$$

$$\ddot{y}_P = a_y = \omega \cdot r \cdot \cancel{2} \left[\cos \frac{\omega t}{2} \cdot \frac{\omega}{2} \cdot \cos \frac{\omega t}{2} + \sin \frac{\omega t}{2} \cdot \cancel{(-\sin \frac{\omega t}{2} \cdot \frac{\omega}{2})} \right]$$

$$\ddot{y}_P = \omega^2 \cdot r \left[\cos^2 \frac{\omega t}{2} - \sin^2 \frac{\omega t}{2} \right]$$

$$\vec{a} = \begin{bmatrix} \ddot{x}_P \\ \ddot{y}_P \end{bmatrix} = \omega^2 \cdot r \begin{bmatrix} 2 \sin \frac{\omega t}{2} \cdot \cos \frac{\omega t}{2} \\ \cos^2 \frac{\omega t}{2} - \sin^2 \frac{\omega t}{2} \end{bmatrix}$$

Kontrolle $r = 30 \text{ mm}$; $\varphi = 90^\circ$; $\frac{\varphi}{2} = 45^\circ$; $\omega = 1 \frac{1}{s}$




$$\vec{a} = 30 \frac{\text{mm}}{\text{s}^2} \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

$$\vec{a} = \begin{bmatrix} 30 \frac{\text{mm}}{\text{s}^2} \\ 0 \end{bmatrix}$$

Beschl. aus Trans + Rot


$$\vec{a}_P = \vec{a}_{n, \text{trans}} + \vec{a}_{t, \text{trans}} + \vec{a}_{n, \text{rot}} + \vec{a}_{t, \text{rot}}$$

$$\vec{a}_P = 0 + 0 + \frac{v^2}{r} + 0$$



Gesamt = Trans + Rot

Für $\varphi = 180^\circ$; $\varphi_2 = 90^\circ$



$$v_P = 30 \frac{\text{mm}}{\text{s}} \begin{bmatrix} 2 \\ 0 \end{bmatrix} = \begin{bmatrix} 60 \frac{\text{mm}}{\text{s}} \\ 0 \end{bmatrix}$$

$$a_P = 30 \frac{\text{mm}}{\text{s}^2} \begin{bmatrix} 0 \\ -1 \end{bmatrix} = \begin{bmatrix} 0 \\ -30 \frac{\text{mm}}{\text{s}^2} \end{bmatrix}$$